

Current Transformer Cabinets

Commonwealth Edison Area Units | UL listed

CT Cabinets with wiring harness and pre-wired meter socket and test switch
Underground Entry and Overhead Exit

Catalog Number	Amps	Voltage	Phase	SCCR	Dimensions		
					H"	W"	D"
CEM-403-6	400	600	1Ø3W	65kA	42	24	8
CEM-433-8	400	600	3Ø3W	65kA	42	24	8
CEM-404-13	400	600	3Ø4W	65kA	42	24	8
CEM-603-6	600	600	1Ø3W	65kA	48	25	10
CEM-633-8	600	600	3Ø3W	65kA	48	25	10
CEM-604-13	600	600	3Ø4W	65kA	48	25	10
CEM-803-6	800	600	1Ø3W	65kA	48	25	10
CEM-833-8	800	600	3Ø3W	65kA	48	25	10
CEM-804-13	800	600	3Ø4W	65kA	48	25	10
CEM-1203-6	1200	600	1Ø3W	85kA	66	42	17
CEM-1233-8	1200	600	3Ø3W	85kA	66	42	17
CEM-1204-13	1200	600	3Ø4W	85kA	66	42	17
CEM-1603-6	1600	600	1Ø3W	85kA	66	42	17
CEM-1633-8	1600	600	3Ø3W	85kA	66	42	17
CEM-1604-13	1600	600	3Ø4W	85kA	66	42	17
CEM-2003-6	2000	600	1Ø3W	85kA	66	42	17
CEM-2033-8	2000	600	3Ø3W	85kA	66	42	17
CEM-2004-13	2000	600	3Ø4W	85kA	66	42	17
CEM-2504-13	2500	600	3Ø4W	85kA	72	42	20
CEM-3004-13	3000	600	3Ø4W	85kA	72	42	20

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



Current Transformer & Disconnect Cabinets

Commonwealth Edison Area Units | UL Listed

Overhead/Underground Entry | Underground Exit

(2) 200 Amp Square D Circuit Breakers

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTJGL22B-413-6	400	120/240	1Ø 3W	65kA	JGL26200	BELOW	66	25	15
CEM-CTJGL22B-434-13	400	208Y/120	3Ø 4W	65kA	JGL36200	BELOW	66	25	15
CEM-CTJGL24B-434-13	400	480Y/277	3Ø 4W	35kA	JGL36200	BELOW	66	25	15
CEM-CTJL24B-434-13	400	480Y/277	3Ø 4W	65kA	JL36200	BELOW	66	25	15

(2) 200 Amp GE Circuit Breakers

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTSFH22B-413-6	400	120/240	1Ø 3W	65kA	SFHA24AT0250	BELOW	66	25	15
CEM-CTSFH22B-434-13	400	208Y/120	3Ø 4W	65kA	SFHA36AT0250	BELOW	66	25	15
CEM-CTSFH24B-434-13	400	480Y/277	3Ø 4W	35kA	SFHA36AT0250	BELOW	66	25	15
CEM-CTSFL24B-434-13	400	480Y/277	3Ø 4W	65kA	SFLA36AT0250	BELOW	66	25	15

(1) 400 Amp Fused Pull-Out

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTPT12B-413-6	400	120/240	1Ø 3W	65kA	PAT-325-2P	BELOW	66	25	15
CEM-CTPT12B-434-13	400	208Y/120	3Ø 4W	65kA	PAT-325	BELOW	66	25	15
CEM-CTPT14B-434-13	400	480Y/277	3Ø 4W	65kA	PAT-365	BELOW	66	25	15

Notes

- Approved for overhead or underground entry and underground exit.
- All cabinets are furnished with a wiring harness and a door-mounted pre-wired meter socket with test switches.
- Fuses - Use class "T" fuses rated 300 volts (Littlefuse JLLN, Bussman JJN, Gould A3T or equal). Fuses are can be provided.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.



Current Transformer & Disconnect Cabinets

Commonwealth Edison Area Units | UL Listed

Overhead & Underground Entry or Underground Exit

(1) 400 Amp Circuit Breakers

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTDK12B-413-6	400	120/240	1Ø3W	65kA	DK2400	BELOW	66	25	15
CEM-CTDK12B-434-13	400	208Y/120	3Ø4W	65kA	DK3400	BELOW	66	25	15
CEM-CTKDB14B-434-13	400	480Y/277	3Ø4W	35kA	KDB3400	BELOW	66	25	15
CEM-CTHKD14B-434-13	400	480Y/277	3Ø4W	65kA	HKD3400	BELOW	66	25	15

(1) 400 Amp Square D Circuit Breakers

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTLGL12B-413-6	400	120/240	1Ø3W	65kA	LGL36400U31X	BELOW	66	25	15
CEM-CTLGL12B-434-13	400	208Y/120	3Ø4W	65kA	LGL36400U31X	BELOW	66	25	15
CEM-CTLGL14B-434-13	400	480Y/277	3Ø4W	35kA	LGL36400U31X	BELOW	66	25	15
CEM-CTLJL14B-434-13	400	480Y/277	3Ø4W	65kA	LJL36400U31X	BELOW	66	25	15

(1) 400 Amp GE Circuit Breakers

Catalog Number	Amps	Voltage	Phase	SCCR	Circuit Breaker		Dimensions		
					Catalog #	Location	H"	W"	D"
CEM-CTSGD12B-413-6	400	120/240	1Ø3W	65kA	SGDA22AT0400	BELOW	66	25	15
CEM-CTSGD12B-434-13	400	208Y/120	3Ø4W	65kA	SGDA32AT0400	BELOW	66	25	15
CEM-CTSGH14B-434-13	400	480Y/277	3Ø4W	35kA	SGHA36AT0400	BELOW	66	25	15
CEM-CTSGL14B-434-13	400	480Y/277	3Ø4W	65kA	SGLA36AT0400	BELOW	66	25	15

Notes

- Approved for overhead or underground entry and underground exit.
- All cabinets are furnished with a wiring harness and a door-mounted pre-wired meter socket with test switches.
- Fuses - Use class "T" fuses rated 300 volts (Littlefuse JLLN, Bussman JJN, Gould A3T or equal). Fuses are can be provided.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

