



UL231 Updates Power Outlet Standards Temporary Power Metering

Key Affected Products

Effective October 1, 2022, updates to UL231 power outlet standards for **Service Equipment Applications** will necessitate changes to UL-listed Milbank product offerings.

Under this standard, key product requirements include, but are not limited to, 'touch-safe' barriers to prevent inadvertent contact with live parts while servicing, as well as a single disconnect operation that de-energizes all circuits.

Common Units Affected *Examples below are not all inclusive



U4908 Series

Prev Catalog #
U4908-O-11GR

New Catalog #
U4908-O-**100MB**-11GR



U5100 Series

Prev Catalog #
U5100-XL-11GR

New Catalog #
U5100-XL-**100MB**-11GR



U5865 Series

Prev Catalog #
U5865-XL-38GBGRW

New Catalog #
U5865-XL-**100MB**-38GBGRW



U4909 Series

Prev Catalog #
U4909-O-11GR

New Catalog #
U4909-O-**100MB**-11GR



U5101 Series

Prev Catalog #
U5101-XL-11GR

New Catalog #
U5101-XL-**100MB**-11GR



U6134 Series

Prev Catalog #
U6134-RL-76GBGR

New Catalog #
U6134-RL-**100MB**-76GBGR

*Catalog Number **-100MB** designates factory included Main Breaker.

UL231 Key Updates



**Touch Safe
Barriers**

Efforts are being made to redesign/modify our products to meet these design requirements, and Temporary Power units are included in these changes. Going forward, they will require a main breaker to be included from the factory.



**Single
Disconnect**

Please contact your local sales rep with any questions.