



400 Amps Meter Mains

Single & Three Phase



U6227-X-400-K3L



U6230-X-400-K7



U6115-X-2/200-K7L

Features

- **Safe & Secure**
 - Barrel lock provision (optional)
 - Easy outside access to main service disconnect in case of emergency
- **Easy Installation**
 - All-in-one enclosure reduces installation time, labor and errors
 - Wall hanging brackets included
 - Overhead/underground service entry
 - Accepts 3", 3 1/2" or 4" hub for overhead applications
- Field-installable fifth terminal available (single phase only; **K3865**)
- **Durable Enclosure**
 - NEMA 3R rated
 - G90 galvanized steel, powder-coated paint protects against corrosion
- **Ideal Applications**
 - Large homes
 - Small office and commercial buildings
- **Heavy Duty Lever Bypass Meter Socket**
- **One 400 Amps Breaker**
 - 1Ø or 3Ø units available
- **UL Listed**
- **Made in the USA**

Additional Features - U6115 & U6416

- Two 200 Amps breakers
- **U6416** is side bussed

Common Applications



Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.





400 Amps Meter Mains

Single & Three Phase

400 Amps | Meter Mains | 4 & 5 Terminals | 1Ø3W | 240 VAC

Catalog Number	Terminals	Service	Hub	Connectors CU/AL	Dimensions			Knockouts			
				Line	D"	W"	H"	1	2	3	4
U6227-X-400-K3L	4	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6227-X-400-K3L-5T6	5	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6227-X-400-K3L-5T9	5	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6228-X-400-K3L	4	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6228-X-400-K3L-5T6	5	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6228-X-400-K3L-5T9	5	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼

Specifications

- Side Bussed Units: U6228
- AIC Rating: 22K AIC at 240 VAC
- 300 Amps breaker: Can be installed from the factory (upon request)

400 Amps | Meter Mains | 7 Terminals | 3Ø4W | 120/208V

Catalog Number	Service	Hub	Connectors CU/AL	Dimensions			Knockouts			
			Line	D"	W"	H"	1	2	3	4
U6229-X-400-K7L	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼
U6230-X-400-K7L	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	6	36¼	34	4	2½	½	¼

400 Amps | Meter Mains with (2) 200 Amps Breakers | 7 Terminal | 3Ø4W | Ringless | 480 VAC

Catalog Number	Service	Hub	Connectors CU/AL	Dimensions			Knockouts			
			Line	D"	W"	H"	1	2	3	4
U6115-X-2/200-K7L	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	7	37¼	34	4	2½	½	¼
U6416-X-2/200-K7L	OH/UG	C.P.	#4-600 kcmil or (2) 1/0 - 250	7	34¼	34	4	2½	½	¼

Specifications

- Side Bussed Units: U6230 & U6416
- AIC Rating: 22K AIC at 240 VAC. And 10K AIC at 480 VAC
- 300 Amps breaker: Can be installed from the factory (upon request)

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

