


CP3A - Slimline



**4 X Level 2
Dual Port EVSE Stations**

Features

- 100-200 Amps
- 120-480V
- 1Ø, 3Ø Capabilities
- 22K AIC Standard
- Utility Approved Meter
- 6, 8, 16 Circuit Load Center
- Separate Sealable & Lockable Customer and Utility Sections

Available in:

50" and 64" Heights
12" and 20" Widths

Suitable for:

Level 1

120V
1-Phase AC
12-16 Amps

Level 2

208V or 240V
1-Phase AC
12-80 Amps (Typ. 32)

**Best
Seller**



Covered or Exposed Meter


Lexan® Window

Meter Socket Compatible
Ring type, Ringless,
non-metered



**Separate
Sealable &
Lockable
Metering
Section**

Side Wireway
Located on left side of pedestal
for utility incoming wire, allowing
pedestal to be mounted with
back as close as 14 inches to
walls or structures.



Pad Mount



**Contact Your
Local Milbank
Rep Today!**



Direct Bury



**Milbank
Enclosed
Controls are
NEMA 3R
Rated!**



**Perfect for
many EV
Charging
Infrastructure
Projects**



**Milbank EC
Cabinets are
UL Listed
508A & 891**



We are a PROUD American Manufacturer