


# CP3B - B Series



5 X Level 2 Dual-Port  
OR 2 x Level 3 Dual-Port  
EVSE Stations

## Features

- 200-800 Amps
- 22K AIC Standard
- Back-fed Main Breaker
- Sub-feed Lugs
- 480V for DCFC Applications
- 120/240V 103W through 277/480V 304W ratings

## Available in:

48" and 60" Heights  
24" and 32" Widths

## Suitable for:

**Level 2**  
208V or 240V  
1-Phase AC  
12-80 Amps (Typ. 32)

**Level 3**  
480V  
1Ø and 3-Phase AC  
100-200 Amps

**Best  
Seller**



**Lexan® Window**

### Meter Hood

Transparent window is included for meter reading purposes

### Utility Approved Meter

Ringless and ring-type, with lever bypass and field installable fifth terminal kit available

Separate sealable & lockable metering section

### Exterior Receptacles

GFCI duplex receptacles

Separate sealable lockable customer section

### Construction

Galvanized Steel, Aluminum, or stainless-steel options. Standard colors available at no additional cost.

**Milbank EC  
Cabinets are  
NEMA 3R Rated  
and UL Listed  
508A & 891**

**Common Usage**  
Street Parking  
Retail  
Apartment Buildings  
Office Buildings



## Save Valuable Labor Hours



**Pad Mount for Easy Installation!**

*Early shipment available upon request.*

**We are a PROUD American Manufacturer**

