



MILBANK
ENERGY AT WORK

CP3B11115A22



| | | | |
|-------------------------------|---|---------------------------|--|
| Catalog Number | CP3B11115A22 | Insulation | No Insulation |
| Marketing Product Description | Ring Type 100 Amperes 240 Volt 4 Terminal Main Circuit-breaker 16 Circuit Loadcenter 22k Mint Green | Mounting | Pad Mount |
| UPC | 784572269699 | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Length (IN) | 17 | Jaw Quantity | 4 Terminal |
| Width (IN) | 16 | Bypass Type | Link Bypass |
| Height (IN) | 48 | Number of Meter Positions | 1 Position |
| Brand Name | Milbank | Equipment Ground | Ground Bar |
| Type | Ring Type Metered Commercial Pedestal | Hub Opening | No Hub Opening |
| Application | Power Distribution | Line Side Wire Range | 4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil |
| Standard | UL Listed;Type 3R | Number Of Receptacles | 0 |
| Voltage Rating | 120/240 Volts Alternating Current | | |
| Amperage Rating | 100 Continuous Ampere | | |
| Phase | 1 Phase | | |
| Frequency Rating | 60 Hertz | | |
| Size | 17L x 16W x 48H | | |
| Number Of Cutouts | 1 | | |
| Cutout Size | One 100 Ampere Main Breaker | | |
| Cable Entry | Underground | | |
| Terminal | Single Mechanical | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.