



MILBANK
ENERGY AT WORK

PB-018-NK



Catalog Number	PB-018-NK	Color	ANSI 61 Gray
Marketing Product Description	800 Ampere 1phase 600 Volt 24in-48in-11in Painted Steel No Knockouts Lift Off Screw Front .5-13 Studs 3 Lug Per Landing - 4-600kcmil 10k Ampere Interrupting Capacity	Connection	1/2 Inch Stud Load Side and 4 AWG to 600 kcmil Line Side Lugs
UPC	784572234253	Construction	G90 Galvanized Steel
Length (IN)	11	Finish	Powder Coat Finish
Width (IN)	24	Number of Positions	1 Position
Height (IN)	48	Number of Phases	1
Weight (LB)	114	Short Circuit Rating	50000 Ampere
Brand Name	Milbank	Miscellaneous	No Knockouts
Type	Line to Load Distribution		
Application	Termination Cabinet		
Standard	UL Listed;Type 3R		
Number Of Conductors	3		
Conductor Material	Copper and Aluminum		
Size	11L x 24W x 48H		
Amperage Rating	Up to 800 Ampere		
Voltage Rating	Up to 600 Volts Alternating Current		
Temperature Rating	No Temperature Rating		
Insulation Material	Polypropylene		
Jacket Material	No Jacket Material		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.