

U5000-XL-76GBGR



Catalog Number	U5000-XL-76GBGR
Marketing Product Description	Unmetered Small Closing Plate TT30 520GR 520GR 1450GB Surface Mount
UPC	784572265608
Length (IN)	5.188
Width (IN)	8.875
Height (IN)	19.25
Brand Name	Milbank
Type	Unmetered Power Supply
Special Features	Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker
Application	RV Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.188L x 8.875W x 19.25H
Number Of Cutouts	3
Cutout Size	Two Single Pole 20 Ampere Breakers and One Double Pole 50 Ampere Ground Fault Breaker

Cable Entry	Overhead or Underground
Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	0 Terminals
Bypass Type	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	14 - 2/0 AWG
Number Branch Circuits	2
Number Of Receptacles	3
Receptacle Configuration	One NEMA 14-50 and Two NEMA 5-20 Ground Fault

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.