



**MILBANK**  
ENERGY AT WORK

## U4549-RXL



Catalog Number	U4549-RXL	Connection	4 AWG to 600 kcmil and 6 AWG to 350 kcmil and 4 AWG to 600 kcmil and Line and Load Side Lugs
Marketing Product Description	400 Ampere 3 Phase 600 Volt 16in-27in-5in Painted Steel Lift Off Front Hasp 5 Lugs Per Landing 10k Short Circuit Current Rating	Construction	G90 Galvanized Steel
UPC	784572230620	Finish	Powder Coat Finish
Length (IN)	5	Number of Positions	1 Position
Width (IN)	15.5	Number of Phases	3
Height (IN)	27	Short Circuit Rating	10000 Ampere
Weight (LB)	36		
Brand Name	Milbank		
Type	Line to Load Distribution		
Application	Termination Cabinet		
Standard	UL Listed;Type 3R		
Number Of Conductors	5		
Conductor Material	Copper and Aluminum		
Size	5L x 15.5W x 27H		
Amperage Rating	Up to 400 Ampere		
Voltage Rating	Up to 600 Volts Alternating Current		
Temperature Rating	No Temperature Rating		
Insulation Material	Polypropylene		
Jacket Material	No Jacket Material		
Color	ANSI 61 Gray		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.