

U1233-X-5T-K3



Marketing Product Description 5 Terminal Ringless Large Closing Plate Single Connector 4-600kcmil UPC 784572133037 Length (IN) 5.188 Width (IN) 34.5 Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Catalog Number	U1233-X-5T-K3
Length (IN) 5.188 Width (IN) 34.5 Height (IN) 14 Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Marketing Product Description	Closing Plate Single
Width (IN) Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	UPC	784572133037
Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts	Length (IN)	5.188
Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Width (IN)	34.5
Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Height (IN)	14
Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Brand Name	Milbank
Standard UL Listed;Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Туре	Ringless Meter Socket
Voltage Rating 300 Volts Alternating Current Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Application	Meter Socket
Amperage Rating 150 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Standard	UL Listed;Type 3R
Phase 1 Phase Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Voltage Rating	300 Volts Alternating Current
Frequency Rating 60 Hertz Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Amperage Rating	150 Continuous Ampere
Size 5.188L x 34.5W x 14H Number Of Cutouts 0	Phase	1 Phase
Number Of Cutouts 0	Frequency Rating	60 Hertz
	Size	5.188L x 34.5W x 14H
	Number Of Cutouts	0
Cutout Size No Main Breaker	Cutout Size	No Main Breaker
Cable Entry Overhead or Underground	Cable Entry	Overhead or Underground
Terminal Single Mechanical	Terminal	Single Mechanical
Insulation Glass Polyester	Insulation	Glass Polyester
Mounting Surface Mount	Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	No Bypass
Number of Meter Positions	3 Positions
Equipment Ground	Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.