



MILBANK
ENERGY AT WORK

U1256-R-KK-EX-RGE



Catalog Number	U1256-R-KK-EX-RGE	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Large Hub Open Horn Bypass 6 Position Overhead Extension Assembly Rochester Gas And Electric	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572227859	Jaw Quantity	4 Terminal
Length (IN)	5.125	Bypass Type	Horn Bypass
Width (IN)	62.875	Number of Meter Positions	6 Positions
Height (IN)	18	Equipment Ground	Ground Lug
Brand Name	Milbank	Hub Opening	Large Hub Opening
Type	Ringless Meter Socket	Load Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	300 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.125L x 62.875W x 18H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead with Center Wireway		
Terminal	3/8 Inch Stud		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.