MILBANK ENERGYAT WORK

U3042-XL-QG-BLG-LIS

T.	e			LANSING MACONE M
				lingin
-				
			e.	
	B			and the second
WARNER With the second	11 II	<u>))</u>		6
			C	
) RE				X
	0	-		

Catalog Number	U3042-XL-QG-BLG-LIS	
Marketing Product Description	5 Terminal Ringless Small Closing Plate Quadplex Ground Lever Bypass 7-8 In Barrel Lock Ground With Bracket Provision Long Island Lighting Company	
UPC	784572194694	
Length (IN)	4.844	
Width (IN)	13	
Height (IN)	19	
Brand Name	Milbank	
Туре	Ringless Meter Socket	
Special Features	Long Island Lighting Company	
Application	Meter Socket	
Standard	UL Listed;Type 3R	
Voltage Rating	600 Volts Alternating Current	
Amperage Rating	200 Continuous Ampere	
Phase	1 Phase	
Frequency Rating	60 Hertz	
Size	4.844L x 13W x 19H	
Number Of Cutouts	0	
Cutout Size	No Main Breaker	
Cable Entry	Overhead or Underground	

Terminal	Lay in
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	Quadplex Ground
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.