




**MILBANK**  
ENERGY AT WORK

## U4142-XT-LIS



Catalog Number	U4142-XT-LIS
Marketing Product Description	5 Terminal Ringless 2 Large Closing Plates Lever Bypass 2 Position Long Island Lighting Company
UPC	784572139398
Length (IN)	6
Width (IN)	32.125
Height (IN)	25.25
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Long Island Lighting Company
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	6L x 32.125W x 25.25H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground with Center Wireway
Terminal	3/8 Inch Stud

Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	2 Positions
Equipment Ground	Ground Lug
Hub Opening	Twin Large Closing Plates
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.