




MILBANK
ENERGY AT WORK

U2693-XL-KK-BL



Catalog Number	U2693-XL-KK-BL	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Marketing Product Description	4 Terminal Ringless Small Closing Plate 3 Position Horn Bypass 9-16 In Barrel Lock With Bracket Provision	Jaw Quantity	4 Terminal
UPC	784572209787	Bypass Type	Horn Bypass
Length (IN)	4.125	Number of Meter Positions	3 Position Vertical Design
Width (IN)	8	Equipment Ground	Ground Lug
Height (IN)	35.719	Hub Opening	Small Closing Plate
Brand Name	Milbank	Line Side Wire Range	6 AWG - 350 kcmil
Type	Ringless Meter Socket	Load Side Wire Range	6 - 2/0 AWG
Application	Meter Socket	Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	300 Volts Alternating Current		
Amperage Rating	100 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.125L x 8W x 35.719H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Lay in		
Insulation	Glass Polyester		
Mounting	Surface Mount		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.