




MILBANK
ENERGY AT WORK

U3525-XL-K2



Catalog Number	U3525-XL-K2
Marketing Product Description	4 Terminal Ring Type Small Closing Plate 5 Position Double Connector 6-350kcmil
UPC	784572164192
Length (IN)	4.5
Width (IN)	49.063
Height (IN)	16
Brand Name	Milbank
Type	Ring Type Meter Socket
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	300 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 49.063W x 16H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	3 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	Two 6 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.