## MILBANK<sup>®</sup> ENERGYAT WORK

## U1748-O-WI



Catalog Number	U1748-O-WI
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass Wisconsin Area
UPC	784572134218
Length (IN)	4.844
Width (IN)	13
Height (IN)	64
Brand Name	Milbank
Туре	Ringless Meter Socket
Special Features	Wisconsin Area
Application	Meter Socket
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	320 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.844L x 13W x 64H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Underground
Terminal	3/8 Inch Stud
Insulation	Glass Polyester
Mounting	Pedestal

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	4 Barrel Ground Lug
Hub Opening	Plain Top
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.