



MILBANK[®]
ENERGY AT WORK

U1748-O-WI



Catalog Number	U1748-O-WI	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass Wisconsin Area	Jaw Quantity	4 Terminal
UPC	784572134218	Bypass Type	Lever Bypass
Length (IN)	4.844	Number of Meter Positions	1 Position
Width (IN)	13	Equipment Ground	4 Barrel Ground Lug
Height (IN)	64	Hub Opening	Plain Top
Brand Name	Milbank	Number Of Receptacles	0
Type	Ringless Meter Socket		
Special Features	Wisconsin Area		
Application	Meter Socket		
Standard	UL Listed;Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	320 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.844L x 13W x 64H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Underground		
Terminal	3/8 Inch Stud		
Insulation	Glass Polyester		
Mounting	Pedestal		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.