




BC518



Catalog Number	BC518	Color	ANSI 61 Gray
Marketing Product Description	800 Ampere 1phase 600 Volt 71in-15in-6in Painted Steel Lift Off Screw Front 2 Lugs Per Landing - 4-600kcmil 4 Lugs Per Landing - 1/0-250kcmil 42k Ampere Interrupting Capacity	Connection	4 AWG to 600 kcmil Line Side Lugs and 6 AWG to 250 kcmil Load Side Lugs
UPC	784572111448	Construction	G90 Galvanized Steel
Length (IN)	6.19	Finish	Powder Coat Finish
Width (IN)	71.56	Number of Positions	5 Positions
Height (IN)	15.5	Number of Phases	1
Weight (LB)	95	Short Circuit Rating	42000 Ampere
Brand Name	Milbank		
Type	Line to Load Distribution		
Application	Bus Gutter		
Standard	UL Listed;Type 3R		
Number Of Conductors	2		
Conductor Material	Copper and Aluminum		
Size	6.19L x 71.56W x 15.5H		
Amperage Rating	Up to 800 Ampere		
Voltage Rating	Up to 600 Volts Alternating Current		
Temperature Rating	No Temperature Rating		
Insulation Material	Polypropylene		
Jacket Material	No Jacket Material		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.