



MILBANK
ENERGY AT WORK

PB-034-NK



Catalog Number	PB-034-NK
Marketing Product Description	400 Ampere 3 Phase 600 Volt 16in-36in-7in Painted Steel No Knockouts Lift Off Screw Front .5-13 Studs 1 Lug Per Landing - 4-600kcmil 10k Ampere Interrupting Capacity
UPC	784572200326
Length (IN)	7
Width (IN)	16.156
Height (IN)	36.078
Weight (LB)	55
Brand Name	Milbank
Type	Line to Load Distribution
Application	Termination Cabinet
Standard	UL Listed;Type 3R
Number Of Conductors	1
Conductor Material	Copper and Aluminum
Size	7L x 16.156W x 36.078H
Amperage Rating	Up to 400 Ampere
Voltage Rating	Up to 600 Volts Alternating Current
Temperature Rating	No Temperature Rating
Insulation Material	Polypropylene
Jacket Material	No Jacket Material

Color	ANSI 61 Gray
Connection	1/2 Inch Stud Line Side and 4 AWG to 600 kcmil Load Side Lugs
Construction	G90 Galvanized Steel
Finish	Powder Coat Finish
Number of Positions	1 Position
Number of Phases	3
Short Circuit Rating	50000 Ampere
Miscellaneous	No Knockouts

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.