

## U5200-XL-75



Catalog Number	U5200-XL-75
Marketing Product Description	Unmetered Small Closing Plate TT30 1450 520GR Single Pedestal Direct Bury
UPC	784572258198
Length (IN)	5.188
Width (IN)	8.688
Height (IN)	64.5
Brand Name	Milbank
Туре	Unmetered Power Supply
Special Features	Single Pole 20 Ampere Breaker and Single Pole 30 Ampere Breaker and Double Pole 50 Ampere Breaker
Application	RV Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.188L x 8.688W x 64.5H
Number Of Cutouts	3

Cutout Size	One Single Pole 20 Ampere Breaker and One Single Pole 30 Ampere Breaker and One Double Pole 50 Ampere Breaker
Cable Entry	Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	0 Terminals
Bypass Type	No Bypass
Bypass Type  Number of Meter Positions	No Bypass Single Power Head
Number of Meter Positions	Single Power Head  2 Barrel Ground Lug and
Number of Meter Positions  Equipment Ground	Single Power Head  2 Barrel Ground Lug and Ground Bar
Number of Meter Positions  Equipment Ground  Hub Opening	Single Power Head  2 Barrel Ground Lug and Ground Bar  Small Closing Plate
Number of Meter Positions  Equipment Ground  Hub Opening  Line Side Wire Range	Single Power Head  2 Barrel Ground Lug and Ground Bar  Small Closing Plate  6 AWG - 350 kcmil

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.