



**MILBANK**<sup>®</sup>  
ENERGY AT WORK

## U5300-O



Catalog Number	U5300-O
Marketing Product Description	4 Terminal Ring Type Plain Top Single Pedestal Direct Bury
UPC	784572258402
Length (IN)	5.313
Width (IN)	8.688
Height (IN)	70.25
Brand Name	Milbank
Type	Ring Type Meter Socket
Application	RV Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.313L x 8.688W x 70.25H
Number Of Cutouts	0
Cutout Size	Breaker Provision
Cable Entry	Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	2 Barrel Ground Lug and Ground Bar
Hub Opening	Plain Top
Line Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	6
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.