

## UQFB-100



Catalog Number	UQFB-100
Marketing Product Description	Milbank 100 Ampere 2 Pole 240 Volt Bolt-on 10k Ampere Interrupting Capacity
UPC	784572146372
Length (IN)	3.281
Width (IN)	3
Height (IN)	7.438
Weight (LB)	3.1
Brand Name	Milbank
Туре	Current Interrupting Device
Special Features	Bolt On
Application	Metering Accessory
Application Standard	Metering Accessory UL Listed
	,
Standard	UL Listed
Standard  Voltage Rating	UL Listed 240 Volts Alternating Current
Standard  Voltage Rating  Current Rating	UL Listed 240 Volts Alternating Current 100 Ampere
Standard  Voltage Rating  Current Rating  Frequency Rating	UL Listed 240 Volts Alternating Current 100 Ampere 60 Hertz
Standard  Voltage Rating  Current Rating  Frequency Rating  Number of Phases	UL Listed 240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase
Standard  Voltage Rating  Current Rating  Frequency Rating  Number of Phases  Frame	UL Listed 240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase F-Frame
Standard  Voltage Rating  Current Rating  Frequency Rating  Number of Phases  Frame  Trip Type	UL Listed 240 Volts Alternating Current 100 Ampere 60 Hertz 1 Phase F-Frame Thermal Magnetic 10,000 Ampere Interrupting

Connection	Lug to Lug
Auxiliary Contacts	No Auxiliary Contacts
Material	Non Metallic
Operating Temperature	40 Degrees Celsius

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.