



MPRV-BLANK-78



| | |
|-------------------------------|-------------------------------------------------------------------------------------|
| Catalog Number | MPRV-BLANK-78 |
| Marketing Product Description | 4 Terminal Ring Type Plain Top 1-main Breaker Provision Single Pedestal Direct Bury |
| UPC | 784572166936 |
| Length (IN) | 4.01 |
| Width (IN) | 8.16 |
| Height (IN) | 78 |
| Brand Name | Milbank |
| Type | Ring Type Meter Socket |
| Application | Meter Socket With Load Center |
| Standard | UL Listed;Type 3R |
| Voltage Rating | Up to 240 Volts Alternating Current |
| Amperage Rating | 100 Continuous Ampere |
| Phase | 1 Phase |
| Frequency Rating | 60 Hertz |
| Size | 4.01L x 8.16W x 78H |
| Number Of Cutouts | 0 |
| Cutout Size | Breaker Provision |
| Cable Entry | Underground |
| Terminal | Double Mechanical |
| Insulation | Fiberglass with Resin |

| | |
|---------------------------|----------------------------------------------|
| Mounting | Pedestal |
| Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Jaw Quantity | 4 Terminal |
| Bypass Type | No Bypass |
| Number of Meter Positions | 1 Position |
| Equipment Ground | Ground Bar |
| Hub Opening | Plain Top |
| Line Side Wire Range | 6 AWG - 350 kcmil |
| Number Branch Circuits | 6 |
| Number Of Receptacles | 0 |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.