

U3494-XL-HSP



Marketing Product Description 4 Terminal Ringless Small Closing Plate 4 Position Stainless Steel Hasp UPC 784572300750 Length (IN) 4.5 Width (IN) 40.688 Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed;Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H Number Of Cutouts 0	Catalog Number	U3494-XL-HSP
Length (IN) 4.5 Width (IN) 40.688 Height (IN) 16 Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Marketing Product Description	Closing Plate 4 Position
Width (IN) 40.688 Height (IN) 16 Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	UPC	784572300750
Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Length (IN)	4.5
Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Width (IN)	40.688
Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Height (IN)	16
Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Brand Name	Milbank
Standard UL Listed;Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Туре	Ringless Meter Socket
Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Application	Meter Socket
Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Standard	UL Listed;Type 3R
Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Voltage Rating	300 Volts Alternating Current
Frequency Rating 60 Hertz Size 4.5L x 40.688W x 16H	Amperage Rating	100 Continuous Ampere
Size 4.5L x 40.688W x 16H	Phase	1 Phase
	Frequency Rating	60 Hertz
Number Of Cutouts 0	Size	4.5L x 40.688W x 16H
	Number Of Cutouts	0
Cutout Size No Main Breaker	Cutout Size	No Main Breaker
Cable Entry Overhead or Underground	Cable Entry	Overhead or Underground
Terminal Lay in	Terminal	Lay in
Insulation Glass Polyester	Insulation	Glass Polyester
Mounting Surface Mount	Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	4 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.