

U3495-XL-HSP



Marketing Product Description Closing Plate 5 Position Stainless Steel Hasp UPC 784572300767 Length (IN) 4.5 Width (IN) 48.875 Height (IN) 16 Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Insulation Glass Polyester	Catalog Number	U3495-XL-HSP
Length (IN) Width (IN) 48.875 Height (IN) 16 Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Marketing Product Description	Closing Plate 5 Position
Width (IN) Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	UPC	784572300767
Height (IN) Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Length (IN)	4.5
Brand Name Milbank Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Width (IN)	48.875
Type Ringless Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Height (IN)	16
Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Brand Name	Milbank
Standard UL Listed;Type 3R Voltage Rating 300 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Туре	Ringless Meter Socket
Voltage Rating Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Application	Meter Socket
Amperage Rating Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Standard	UL Listed;Type 3R
Phase 1 Phase Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Voltage Rating	300 Volts Alternating Current
Frequency Rating 60 Hertz Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Amperage Rating	100 Continuous Ampere
Size 4.5L x 48.875W x 16H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Phase	1 Phase
Number Of Cutouts Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Frequency Rating	60 Hertz
Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Size	4.5L x 48.875W x 16H
Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Number Of Cutouts	0
Terminal Lay in Insulation Glass Polyester	Cutout Size	No Main Breaker
Insulation Glass Polyester	Cable Entry	Overhead or Underground
	Terminal	Lay in
Mounting Surface Mount	Insulation	Glass Polyester
Surface Mount	Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass
Number of Meter Positions	5 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.