

## U8036-XL-KK



	Terminal Ringless Small
P	Closing Plate Horn Bypass 6 Position
PC 7	784572141896
ength (IN) 4	1.5
/idth (IN) 5	57.25
leight (IN)	6
rand Name N	Milbank
ype R	Ringless Meter Socket
pplication N	Meter Socket
tandard U	JL Listed;Type 3R
oltage Rating 3	800 Volts Alternating Current
mperage Rating 1	00 Continuous Ampere
hase 1	Phase
requency Rating 6	00 Hertz
ize 4	I.5L x 57.25W x 16H
lumber Of Cutouts 0	)
utout Size N	No Main Breaker
able Entry C	Overhead or Underground
erminal La	ay in
nsulation G	Glass Polyester
Nounting S	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	6 Positions
Equipment Ground	Ground Lug
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 - 2/0 AWG
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.