


U2736-XT-K8



Catalog Number	U2736-XT-K8
Marketing Product Description	7 Terminal Ringless 2 Large Closing Plates Lever Bypass 6 Position Double Connector 4-600kcmil
UPC	784572320963
Length (IN)	6
Width (IN)	72.375
Height (IN)	31.25
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket
Standard	UL Listed; Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	3 Phase
Frequency Rating	60 Hertz
Size	6L x 72.375W x 31.25H
Number Of Cutouts	0
Cutout Size	No Main Breaker
Cable Entry	Overhead or Underground with Center Wireway
Terminal	Double Mechanical
Insulation	Glass Polyester

Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	7 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	6 Positions
Equipment Ground	Ground Lug
Hub Opening	Twin Large Closing Plates
Line Side Wire Range	Two 2 AWG - 600 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

