

U4383-XL-5T-BLG



Marketing Product Description S Terminal Ringless Small Closing Plate 3 Position 7-8 In Barrel Lock Ground With Bracket Provision UPC 784572285996 Length (IN) 4.188 Width (IN) 12 Height (IN) 31.5 Brand Name Milbank Type Ring Type Meter Socket Application Meter Socket Standard UL Listed;Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Catalog Number	U4383-XL-5T-BLG
Length (IN) 4.188 Width (IN) 12 Height (IN) 31.5 Brand Name Milbank Type Ring Type Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Marketing Product Description	Closing Plate 3 Position 7-8 In Barrel Lock Ground With
Width (IN) 12 Height (IN) 31.5 Brand Name Milbank Type Ring Type Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	UPC	784572285996
Height (IN) Brand Name Milbank Type Ring Type Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Length (IN)	4.188
Brand Name Milbank Type Ring Type Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Width (IN)	12
Type Ring Type Meter Socket Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Height (IN)	31.5
Application Meter Socket Standard UL Listed; Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Brand Name	Milbank
Standard UL Listed;Type 3R Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Туре	Ring Type Meter Socket
Voltage Rating 600 Volts Alternating Current Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Application	Meter Socket
Amperage Rating 100 Continuous Ampere Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Standard	UL Listed;Type 3R
Phase 1 Phase Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Voltage Rating	600 Volts Alternating Current
Frequency Rating 60 Hertz Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Amperage Rating	100 Continuous Ampere
Size 4.188L x 12W x 31.5H Number Of Cutouts 0 Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Phase	1 Phase
Number Of Cutouts0Cutout SizeNo Main BreakerCable EntryOverhead or UndergroundTerminalLay inInsulationGlass Polyester	Frequency Rating	60 Hertz
Cutout Size No Main Breaker Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Size	4.188L x 12W x 31.5H
Cable Entry Overhead or Underground Terminal Lay in Insulation Glass Polyester	Number Of Cutouts	0
Terminal Lay in Insulation Glass Polyester	Cutout Size	No Main Breaker
Insulation Glass Polyester	Cable Entry	Overhead or Underground
·	Terminal	Lay in
	Insulation	Glass Polyester
Mounting Surface Mount	Mounting	Surface Mount

Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	No Bypass
Number of Meter Positions	3 Positions
Equipment Ground	3 Barrel Ground Lug and Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 250 kcmil
Load Side Wire Range	6 - 2/0 AWG
Barrel Lock Provision	7/8 Inch Knockout and Angle Bracket For Barrel Lock Provision
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.