

## FD727318-FT



Marketing Product Description  72x18x73.75 Hinge Cover Type 12 Steel No Knockouts ANSI 61 Gray Flange Disconnect Double Doors Handle Each Door  UPC  784572277670  Length (IN)  18  Width (IN)  73.75  Height (LB)  845  Brand Name  Milbank  Type  Flanged Disconnect  Application  Enclosure for Mounting Electrical Equipment  Standard  UL Listed  Number Of Outlet  0  Material  Steel with Powder Coat Finish Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting Floor Mount  NEMA Rating  Type 12	Catalog Number	FD727318-FT
Length (IN)  18  Width (IN)  73.75  Height (IN)  72  Weight (LB)  Brand Name  Milbank  Type  Flanged Disconnect  Application  Enclosure for Mounting Electrical Equipment  Standard  UL Listed  Number Of Outlet  0  Material  Steel with Powder Coat Finish  Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting  Floor Mount	Marketing Product Description	Type 12 Steel No Knockouts ANSI 61 Gray Flange Disconnect Double Doors
Width (IN) 73.75  Height (IN) 72  Weight (LB)  Brand Name Milbank  Type Flanged Disconnect  Application Enclosure for Mounting Electrical Equipment  Standard UL Listed  Number Of Outlet 0  Material Steel with Powder Coat Finish Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	UPC	784572277670
Height (IN)  Weight (LB)  Brand Name  Milbank  Type  Flanged Disconnect  Application  Enclosure for Mounting Electrical Equipment  Standard  UL Listed  Number Of Outlet  0  Material  Steel with Powder Coat Finish  Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting  Floor Mount	Length (IN)	18
Weight (LB) 845  Brand Name Milbank  Type Flanged Disconnect  Application Enclosure for Mounting Electrical Equipment  Standard UL Listed  Number Of Outlet 0  Material Steel with Powder Coat Finish  Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Width (IN)	73.75
Brand Name Milbank  Type Flanged Disconnect  Application Enclosure for Mounting Electrical Equipment  Standard UL Listed  Number Of Outlet 0  Material Steel with Powder Coat Finish  Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Height (IN)	72
Type Flanged Disconnect  Application Enclosure for Mounting Electrical Equipment  Standard UL Listed  Number Of Outlet 0  Material Steel with Powder Coat Finish  Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Weight (LB)	845
Application  Enclosure for Mounting Electrical Equipment  Standard  UL Listed  Number Of Outlet  O  Material  Steel with Powder Coat Finish  Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting  Floor Mount	Brand Name	Milbank
Standard  UL Listed  Number Of Outlet  O  Material  Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting  Floor Mount	Туре	Flanged Disconnect
Number Of Outlet  Material  Steel with Powder Coat Finish  Size  18L x 73.75W x 72H  Color  ANSI 61 Gray  Construction  Welded  Cable Entry  No Knockouts  Mounting  Floor Mount	Application	
Material Steel with Powder Coat Finish Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Standard	UL Listed
Size 18L x 73.75W x 72H  Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Number Of Outlet	0
Color ANSI 61 Gray  Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Material	Steel with Powder Coat Finish
Construction Welded  Cable Entry No Knockouts  Mounting Floor Mount	Size	18L x 73.75W x 72H
Cable Entry No Knockouts  Mounting Floor Mount	Color	ANSI 61 Gray
Mounting Floor Mount	Construction	Welded
	Cable Entry	No Knockouts
NEMA Rating Type 12	Mounting	Floor Mount
	NEMA Rating	Type 12

Hinge Type	Continuous Hinge with Removable Pin
Тор	Plain Top
Door	Gasketed Door
Latch	Padlocking Handle with Defeater Mechanism
Support	Body Stiffeners

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.