







QN2200



Catalog Number	QN2200	Connection	Bus to Lug
Marketing Product Description	Siemens 200 Ampere 2 Pole 240 Volt Plug-in 10k Ampere Interrupting Capacity	Auxiliary Contacts	No Auxiliary Contacts
UPC	784572369467	Material	Non Metallic
Length (IN)	3.068	Operating Temperature	40 Degrees Celsius
Width (IN)	1.97		
Height (IN)	6.969		
Weight (LB)	2		
Brand Name	Milbank		
Type	Current Interrupting Device		
Special Features	Plug On		
Application	Metering Accessory		
Standard	UL Listed		
Voltage Rating	240 Volts Alternating Current		
Current Rating	200 Ampere		
Frequency Rating	60 Hertz		
Number of Phases	1 Phase		
Frame	Small Frame		
Trip Type	Thermal Magnetic		
Interrupt Rating	10,000 Ampere Interrupting Capacity		
Number Of Poles	2		
Actuator	Lever		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.



All dimensions are $\pm 1/16"$.
Drawing views are not to scale.

Version:

1

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.