



MILBANK
ENERGY AT WORK

M400-APS-BS



Catalog Number	M400-APS-BS	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ring Type Small Hub Open Link Bypass 1-200 Ampere Main Breaker 4 Branch Circuit	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572325234	Jaw Quantity	4 Terminal
Length (IN)	6	Bypass Type	Link Bypass
Width (IN)	11.5	Number of Meter Positions	1 Position
Height (IN)	47	Equipment Ground	3 Barrel Ground Lug
Brand Name	Milbank	Hub Opening	Small Hub Opening
Type	Ring Type Meter Socket	Number Branch Circuits	1
Application	Meter Socket With Main	Number Of Receptacles	0
Standard	UL Listed;Type 3R		
Voltage Rating	Up to 240 Volts Alternating Current		
Amperage Rating	320 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	6L x 11.5W x 47H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Overhead		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.