



MILBANK
ENERGY AT WORK

U4667-X-8043-DPL



Catalog Number	U4667-X-8043-DPL	Insulation	Glass Polyester
Marketing Product Description	7 Terminal Bolt-in Large Closing Plate Link Bypass 3-double Connector 6-350kcmil Delmarva Power And Light	Mounting	Surface Mount
UPC	784572478695	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	6	Jaw Quantity	7 Terminal
Width (IN)	20.25	Bypass Type	Link Bypass
Height (IN)	34	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	2 Barrel Ground Lug
Type	Bolt On Meter Socket	Hub Opening	Large Closing Plate
Special Features	Delmarva Power and Light	Number Of Receptacles	0
Application	Meter Socket		
Standard	UL Listed;Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	480 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	6L x 20.25W x 34H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	1/2 Inch Stud Line Side		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.