

UCSS3433-O







Catalog Number	UCSS3433-O	Jaw Quantity	13 Terminal
Marketing Product Description	13 Terminal Ring Type Plain Top Test Switch Provision Stainless Steel	Bypass Type	No Bypass
UPC	784572538498	Number of Meter Positions	1 Position
Length (IN)	5.125	Equipment Ground	Ground Lug
Width (IN)	12	Hub Opening	Plain Top
Height (IN)	20	Number Of Receptacles	0
Brand Name	Milbank		
Type	Ring Type Meter Socket		
Application	Meter Socket		
Standard	UL Listed; Type 3R		
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	20 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	5.125L x 12W x 20H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Underground		
Terminal	Single Mechanical		
Insulation	Glass Polyester		
Mounting	Surface Mount		
Enclosure	Unpainted 304 Stainless Steel		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

FEATURE TABLE

ITEM	QTY	DESCRIPTION
A	4	STD. MNTG. EMBOS



All dimensions are +/- 1/16".
Drawing views are not to scale.

Version:

1

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.