




MILBANK[®]
ENERGY AT WORK

U5898-O-100



Catalog Number	U5898-O-100	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless Plain Top 1 100 Ampere Main Breaker 10 Circuit Side Wireway	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572594746	Jaw Quantity	4 Terminal
Length (IN)	4.5	Bypass Type	No Bypass
Width (IN)	17	Number of Meter Positions	1 Position
Height (IN)	34.5	Equipment Ground	Ground Bar
Brand Name	Milbank	Hub Opening	Plain Top
Type	Ringless Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket With Main And Load Center	Load Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Number Branch Circuits	8
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	4.5L x 17W x 34.5H		
Number Of Cutouts	1		
Cutout Size	One 100 Ampere Main Breaker		
Cable Entry	Underground		
Terminal	Lay in		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.