



**MILBANK**  
ENERGY AT WORK

## U4910-O-BL-ALT



Catalog Number	U4910-O-BL-ALT	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Marketing Product Description	7 Terminal Ringless Plain Top Lever Bypass 9-16 In Barrel Lock With Bracket Provision Alliant Energy	Jaw Quantity	7 Terminal
UPC	784572596566	Bypass Type	Lever Bypass
Length (IN)	5.75	Number of Meter Positions	1 Position
Width (IN)	16	Equipment Ground	Ground Lug
Height (IN)	22	Hub Opening	Plain Top
Brand Name	Milbank	Line Side Wire Range	6 AWG - 350 kcmil
Type	Ringless Meter Socket	Load Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket	Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Standard	UL Listed;Type 3R	Number Of Receptacles	0
Voltage Rating	600 Volts Alternating Current		
Amperage Rating	200 Continuous Ampere		
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	5.75L x 16W x 22H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Underground		
Terminal	Lay in		
Insulation	Glass Polyester		
Mounting	Surface Mount		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.