



MILBANK
ENERGY AT WORK

U4807-X-21-BLG



Catalog Number	U4807-X-21-BLG	Insulation	Glass Polyester
Marketing Product Description	13 Terminal Ringless Large Closing Plate Test Switch Prewired 200-400 Ampere Painted Steel Single Front Piano Hinge Cover Hasp Current Transformer Mounting Included 277-480 Volt	Mounting	Surface Mount
UPC	784572603295	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Length (IN)	10	Jaw Quantity	13 Terminal
Width (IN)	21	Bypass Type	No Bypass
Height (IN)	41	Number of Meter Positions	1 Position
Brand Name	Milbank	Equipment Ground	Ground Lug
Type	Ringless Meter Socket	Hub Opening	Large Closing Plate
Application	Meter Socket	Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Voltage Rating	600 Volts Alternating Current	Barrel Lock Provision	7/8 Inch Knockout and Angle Bracket For Barrel Lock Provision
Amperage Rating	400 Continuous Ampere	Number Of Receptacles	0
Phase	3 Phase		
Frequency Rating	60 Hertz		
Size	10L x 21W x 41H		
Number Of Cutouts	0		
Cutout Size	No Main Breaker		
Cable Entry	Overhead or Underground		
Terminal	Single Mechanical		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.