






U5950-O-55



Catalog Number	U5950-O-55	Terminal	Double Mechanical
Marketing Product Description	Unmetered Plain Top 1450 520GR Single Pedestal Direct Bury	Insulation	Glass Polyester
UPC	784572605909	Mounting	Pedestal
Length (IN)	7.5	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	8	Jaw Quantity	0 Terminals
Height (IN)	60	Bypass Type	No Bypass
Brand Name	Milbank	Number of Meter Positions	Single Power Head
Type	Unmetered Power Supply	Equipment Ground	2 Barrel Ground Lug and Ground Bar
Special Features	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Breaker	Hub Opening	Plain Top
Application	RV Power	Number Branch Circuits	3
Standard	UL Listed; Type 3R	Number Of Receptacles	2
Voltage Rating	Up to 240 Volts Alternating Current	Receptacle Configuration	One NEMA 14-50 and One NEMA 5-20 Ground Fault
Amperage Rating	100 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	7.5L x 8W x 60H		
Number Of Cutouts	2		
Cutout Size	One Single Pole 20 Ampere Breaker and One Double Pole 50 Ampere Breaker		
Cable Entry	Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.



All dimensions are $\pm 1/16$ ".
Drawing views are not to scale.

Version:

1

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility, and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.