



MILBANK
ENERGY AT WORK

U5891-X-2/200-MLK-BL



| | | | |
|-------------------------------|---|---------------------------|--|
| Catalog Number | U5891-X-2/200-MLK-BL | Terminal | 3/8 Inch Stud |
| Marketing Product Description | 4 Terminal Ringless Large Closing Plate 2-200 Ampere Main Breaker Main Lug Kit 9-16 In Barrel Lock With Bracket Provision | Insulation | Glass Polyester |
| UPC | 784572607842 | Mounting | Surface Mount |
| Length (IN) | 6 | Enclosure | G90 Galvanized Steel with Powder Coat Finish |
| Width (IN) | 29.5 | Jaw Quantity | 4 Terminal |
| Height (IN) | 35 | Bypass Type | Lever Bypass |
| Brand Name | Milbank | Number of Meter Positions | 1 Position |
| Type | Ringless Meter Socket | Equipment Ground | 3 Barrel Ground Lug |
| Application | Meter Socket With Main And Load Center | Hub Opening | Large Closing Plate |
| Standard | UL Listed;Type 3R | Load Side Wire Range | 1 AWG - 300 kcmil |
| Voltage Rating | Up to 240 Volts Alternating Current | Barrel Lock Provision | 9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision |
| Amperage Rating | 320 Continuous Ampere | Number Branch Circuits | 10 |
| Phase | 1 Phase | Number Of Receptacles | 0 |
| Frequency Rating | 60 Hertz | | |
| Size | 6L x 29.5W x 35H | | |
| Number Of Cutouts | 2 | | |
| Cutout Size | Two 200 Ampere Main Breakers | | |
| Cable Entry | Overhead and Underground and Side Wireway | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.