

U7043-XL-TG-KK-IL-5T9W



U7043-XL-TG-KK-IL-5T9W
5 Terminal Ringless Small Closing Plate Triplex Ground Horn Bypass 7-16 In Knockouts Lock Provision 5 Terminal 9 Oclock Position With Wire
784572652316
4.84
13
15.5
Milbank
Ringless Meter Socket
Meter Socket
UL Listed;Type 3R
600 Volts Alternating Current
200 Continuous Ampere
1 Phase
60 Hertz
4.84L x 13W x 15.5H
0
No Main Breaker
Overhead or Underground
Lay in

Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Horn Bypass
Number of Meter Positions	1 Position
Equipment Ground	Triplex Ground
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Barrel Lock Provision	7/16 Inch Knockout for Barrel Lock Provision
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.

FEATURE TABLE			
ITEM	QTY	DESCRIPTION	
Α	6	U/L MNTG.EMBOSS	
В	1	1/4, 1/2 CONC. K.O.	
С	3	1¼, 1½, 2, 2½, 3 CONC. K.O.	
D	3	1, 1¼, 1½, 2, 2½ CONC. K.O.	
E	1	1/4 SOLID K.O.	

