



MILBANK
ENERGY AT WORK



U6123-X-BL

Catalog Number	U6123-X-BL
Marketing Product Description	4 Terminal Ringless 3 Position Condo With House Panel Lever And Barrel Lock Provision
UPC	784572668713
Length (IN)	5.969
Width (IN)	36.5
Height (IN)	30.5
Brand Name	Milbank
Type	Ringless Meter Socket
Application	Meter Socket With Main
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	125 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.969L x 36.5W x 30.5H
Number Of Cutouts	3
Cutout Size	Breaker Provision
Cable Entry	Overhead or Underground
Terminal	Single Mechanical
Insulation	Glass Polyester

Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	4 Terminal
Bypass Type	No Bypass on Residential Meter and Lever Bypass on Common Area Meter
Number of Meter Positions	3 Positions
Equipment Ground	Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	1 AWG - 300 kcmil
Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.