



**MILBANK**  
ENERGY AT WORK



## U6124-X-BL

Catalog Number	U6124-X-BL	Mounting	Surface Mount
Marketing Product Description	4 Terminal Ringless 4 Position Condo With House Panel Lever And Barrel Lock Provision	Enclosure	G90 Galvanized Steel with Powder Coat Finish
UPC	784572668737	Jaw Quantity	4 Terminal
Length (IN)	5.969	Bypass Type	No Bypass on Residential Meter and Lever Bypass on Common Area Meter
Width (IN)	44.813	Number of Meter Positions	4 Positions
Height (IN)	30.5	Equipment Ground	Ground Lug
Brand Name	Milbank	Hub Opening	Large Closing Plate
Type	Ringless Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Application	Meter Socket With Main	Load Side Wire Range	1 AWG - 300 kcmil
Standard	UL Listed;Type 3R	Barrel Lock Provision	9/16 Inch Knockout and Angle Bracket for Barrel Lock Provision
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	125 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	5.969L x 44.813W x 30.5H		
Number Of Cutouts	4		
Cutout Size	Breaker Provision		
Cable Entry	Overhead or Underground		
Terminal	Single Mechanical		
Insulation	Glass Polyester		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.