



MILBANK
ENERGY AT WORK

NU8980-O-200-KK-CECHA



Catalog Number	NU8980-O-200-KK-CECHA	Terminal	Single Mechanical
Marketing Product Description	4 Terminal Ringless Plain Top Horn Bypass 1-200 Ampere Main Breaker Single Pedestal Direct Bury Commonwealth Edison Chicago Housing Authority	Insulation	Glass Polyester
UPC	784572674110	Mounting	Pedestal
Length (IN)	6	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	9	Jaw Quantity	4 Terminal
Height (IN)	79	Bypass Type	Horn Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	2 Barrel Ground Lug
Application	Meter Socket With Main And Load Center	Hub Opening	Plain Top
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Of Receptacles	0
Amperage Rating	200 Continuous Ampere		
Phase	1 Phase		
Frequency Rating	60 Hertz		
Size	6L x 9W x 79H		
Number Of Cutouts	1		
Cutout Size	One 200 Ampere Main Breaker		
Cable Entry	Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.