



MILBANK
ENERGY AT WORK

UAP6095-O-NES



| | | | |
|-------------------------------|---|------------|---|
| Catalog Number | UAP6095-O-NES | Hinge Type | Lift Off Hinges |
| Marketing Product Description | Aluminum Painted Shell 22 Position Per Phase Bar 500 Kcmil Penta Bolt | Top | Plain Top |
| UPC | 784572703926 | Door | Hinged Cover |
| Length (IN) | 16 | Latch | Padlocking Handle with 3 Point Latch Assembly |
| Width (IN) | 32.375 | Support | Body Stiffeners |
| Height (IN) | 43 | | |
| Weight (LB) | 138 | | |
| Brand Name | Milbank | | |
| Type | Terminal Box | | |
| Special Features | 4000 Ampere; Three Phase Four Wire; Penta Bolt; 10,000 Short Circuit Current Rating | | |
| Application | Terminate Conductors | | |
| Standard | UL Listed | | |
| Number Of Outlet | 0 | | |
| Material | Aluminum | | |
| Size | 16L x 32.375W x 43H | | |
| Color | ANSI 61 Gray | | |
| Construction | Welded | | |
| Cable Entry | No Knockouts | | |
| Mounting | Pad Mount or Wall Mount | | |
| NEMA Rating | Type 3R | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.