



# U5892-X-2/200-K3L-5T6-MLK-AMS



Catalog Number	U5892-X-2/200-K3L-5T6-MLK-AMS
Marketing Product Description	5 Terminal Ringless Large Closing Plate Lever Bypass 2-200 Ampere Main Breaker 20 Branch Circuit Single Connector 4-600kcmil Ameren
UPC	784572705104
Length (IN)	5.97
Width (IN)	29.5
Height (IN)	35
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Ameren Energy
Application	Meter Socket With Main And Load Center
Standard	UL Listed;Type 3R
Voltage Rating	600 Volts Alternating Current
Amperage Rating	320 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	5.97L x 29.5W x 35H
Number Of Cutouts	2
Cutout Size	Two 200 Ampere Main Breakers

Cable Entry	Overhead or Underground
Terminal	Single Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	3 Barrel Ground Lug
Hub Opening	Large Closing Plate
Line Side Wire Range	4 AWG - 600 kcmil or Two 1/0 AWG - 250 kcmil
Load Side Wire Range	1 AWG - 300 kcmil
Number Branch Circuits	22
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.