



# U6012-XL-100-K1-5T6-AMS



Catalog Number	U6012-XL-100-K1-5T6-AMS
Marketing Product Description	5 Terminal Ringless Small Closing Plates Lever Bypass 1-100 Ampere Main Breaker 10 Branch Circuit Single Connector 6-350kcmil 5th Terminal 6 O'clock Position Ameren
UPC	784572721579
Length (IN)	4.5
Width (IN)	14.13
Height (IN)	39.25
Brand Name	Milbank
Type	Ringless Meter Socket
Special Features	Ameren Energy
Application	Meter Socket With Main And Load Center
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	100 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	4.5L x 14.13W x 39.25H
Number Of Cutouts	1
Cutout Size	One 100 Ampere Main Breaker

Cable Entry	Overhead or Underground
Terminal	Single Mechanical
Insulation	Glass Polyester
Mounting	Surface Mount
Enclosure	G90 Galvanized Steel with Powder Coat Finish
Jaw Quantity	5 Terminal
Bypass Type	Lever Bypass
Number of Meter Positions	1 Position
Equipment Ground	Ground Bar
Hub Opening	Small Closing Plate
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	6 AWG - 350 kcmil
Number Branch Circuits	8
Number Of Receptacles	0

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.