



**MILBANK**  
ENERGY AT WORK

## U6221-O-100-10GR



Catalog Number	U6221-O-100-10GR	Insulation	Glass Polyester
Marketing Product Description	4 Terminal Ringless Plain Top Lever Bypass 1-100 Ampere Main Breaker 520GR Single Pedestal Direct Bury	Mounting	Pedestal
UPC	784572747456	Enclosure	Aluminum with Powder Coat Finish
Length (IN)	10	Jaw Quantity	4 Terminal
Width (IN)	11	Bypass Type	Lever Bypass
Height (IN)	80	Number of Meter Positions	Single Power Head
Brand Name	Milbank	Equipment Ground	4 Barrel Ground Lug
Type	Ringless Meter Socket	Hub Opening	Plain Top
Application	Meter Socket	Line Side Wire Range	6 AWG - 350 kcmil
Standard	UL Listed;Type 3R	Load Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Number Branch Circuits	6
Amperage Rating	200 Continuous Ampere	Number Of Receptacles	1
Phase	1 Phase	Receptacle Configuration	One NEMA 5-20 Ground Fault
Frequency Rating	60 Hertz		
Size	10L x 11W x 80H		
Number Of Cutouts	2		
Cutout Size	One 100 Ampere Main Breaker and One Single Pole 20 Ampere Breaker		
Cable Entry	Underground		
Terminal	Lay in		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.