



MILBANK
ENERGY AT WORK

U6281-XL-100-5T9



Catalog Number	U6281-XL-100-5T9	Terminal	Lay in
Marketing Product Description	5 Terminal Ringless Small Closing Plate Lever Bypass 1-100 Ampere Main Breaker 10 Branch Circuit 5th Terminal 9 O'clock Position 14.125 In X 34 In X 4.5 In	Insulation	Glass Polyester
UPC	784572771413	Mounting	Surface Mount
Length (IN)	4.5	Enclosure	G90 Galvanized Steel with Powder Coat Finish
Width (IN)	14.125	Jaw Quantity	5 Terminal
Height (IN)	34	Bypass Type	Lever Bypass
Brand Name	Milbank	Number of Meter Positions	1 Position
Type	Ringless Meter Socket	Equipment Ground	Ground Bar
Application	Meter Socket With Main And Load Center	Hub Opening	Small Closing Plate
Standard	UL Listed;Type 3R	Line Side Wire Range	6 AWG - 350 kcmil
Voltage Rating	Up to 240 Volts Alternating Current	Load Side Wire Range	6 AWG - 350 kcmil
Amperage Rating	100 Continuous Ampere	Number Branch Circuits	8
Phase	1 Phase	Number Of Receptacles	0
Frequency Rating	60 Hertz		
Size	4.5L x 14.125W x 34H		
Number Of Cutouts	1		
Cutout Size	One 100 Ampere Main Breaker		
Cable Entry	Overhead or Underground		

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.