



MILBANK
ENERGY AT WORK

AP6348-O



Catalog Number	AP6348-O
Marketing Product Description	2000 Ampere 48H x 28.875L x 30.75W Aluminum Shell Copper Bus Bars 13 Position Per Phase And Neutral
UPC	784572833203
Length (IN)	28.875
Width (IN)	30.75
Height (IN)	48
Weight (LB)	158
Brand Name	Milbank
Type	Line to Load Distribution
Application	Termination Cabinet
Standard	Non UL Listed
Number Of Conductors	13
Conductor Material	Copper and Aluminum
Size	28.875L x 30.75W x 48H
Amperage Rating	Up to 2000 Ampere
Voltage Rating	Up to 600 Volts Alternating Current
Temperature Rating	No Temperature Rating
Insulation Material	Haysite
Jacket Material	Polypropylene
Color	ANSI 61 Gray

Connection	NEMA Spaced Mounting Holes
Construction	G90 Galvanized Steel
Conductor Size	NEMA Spaced Mounting Holes
Finish	Powder Coat Finish
Number of Phases	3

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.